



# TAMIL NADU GOVERNMENT GAZETTE

PUBLISHED BY AUTHORITY

No. 1]

CHENNAI, WEDNESDAY, JANUARY 7, 2015  
Margazhi 23, Jaya, Thiruvalluvar Aandu – 2045

## Part III—Section 2

Statutory Notifications and Orders issued by  
Heads of Departments.

NOTIFICATIONS BY HEADS OF DEPARTMENTS, ETC.

### CONTENTS

Pages.

#### INDIAN RAILWAYS

Energisation of conventional Overhead Equipment on the newly laid track, as part of doubling between Tiruchirappalli and Manaparai Stations, from OHE Mast Location No. 340/47 (km/ch:340/978.40) to OHE Mast location No. 377/27 (km/ch : 377/580.50) at 25 kV, 50 Hz, ac single phase system on Tiruchirappalli - Dindigul Section in Tiruchirappalli and Madurai Divisions of Southern Railway, etc. .. .. .

2 - 4

## NOTIFICATIONS BY HEADS OF DEPARTMENTS, ETC.

### INDIAN RAILWAYS

**Energisation of conventional Overhead Equipment on the newly laid track, as part of doubling between Tiruchirappalli and Manaparai Stations, from OHE Mast Location No. 340/47 (km/ch:340/978.40) to OHE Mast Location No. 377/27 (km/ch : 377/580.50) at 25 kV, 50 Hz, ac single phase system on Tiruchirappalli - Dindigul Section in Tiruchirappalli and Madurai Divisions of Southern Railway.**

(No. E.320/X/RVNL/CRS.)

(Pro forma 10-01)

“PUBLIC NOTIFICATION”

No. SRO C-1/2015.

Notice is hereby given to all users of Railway lines and premises situated on the completed section of the under-noted section of the Southern Railway that the 25000 Volt, 50 Hz, ac, single phase overhead traction wires will be energised on or after the date specified against the Section. On and from the same date the overhead traction line shall be treated as “LIVE” at all times and no unauthorised person shall approach or work in the proximity of the said overhead line.

<i>Section</i>	<i>Date</i>
Energisation of conventional Overhead Equipment on the newly laid track, as part of doubling between Tiruchirappalli and Manaparai Stations, from OHE Mast location No. 340/47(km/ch:340/978.40) to OHE Mast location No. 377/27 (km/ch : 377/580.50) at 25 kV, 50 Hz, ac single phase system on Tiruchirappalli - Dindigul Section in Tiruchirappalli and Madurai Divisions of Southern Railway.	31-12-2014

Chennai-600 008,  
30th December 2014.

P. MANI,  
*Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.*

(No. E.320/X/RVNL/CRS.)

### INTRODUCTION OF ac 25 kV TRACTION

(Pro forma 10-02)

“WARNING TO ROAD USERS”

No. SRO C-2/2015.

It is notified for information of the public that in connection with introduction of 25 kV ac electric traction on the newly laid track, as part of doubling between Tiruchirappalli and Manaparai Stations, from OHE Mast location No. 340/47 (km/ch: 340/978.40) to OHE Mast location No. 377/27 (km/ch:377/580.50) at 25 kV, 50 Hz, ac single phase system on Tiruchirappalli - Dindigul Section in Tiruchirappalli and Madurai Divisions of Southern Railway, height gauges have been erected at all the level crossings with clear height of 4.67 m above road level with a view to prevent loads of excessive height from coming into contact or dangerous proximity to live traction wires.

Public are hereby notified to observe the height specified above for the purpose of loading vehicles and to see that the loads carried in road vehicles do not infringe the height gauges under any circumstances.

The dangers of a load of excessive height are as follows:

- i.* Danger to the height gauge and consequent obstruction to the road as well as the Railway line.
- ii.* Danger to the Materials or equipment carried or for the vehicle itself.
- iii.* Danger of fire and risk of life due to contact with or dangerous proximity to the conductors.

Chennai-600 008,  
30th December 2014.

P. MANI,  
*Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.*

**Energisation of Overhead Equipment on the newly laid track, as part of doubling, between Villupuram and Vriudhachalam Town Stations, from OHE Mast No. 163/45A (km/ch:163/693.55) to OHE Mast No. 218/40 (km/ch : 218/978.85) at 25 kV, 50 Hz, ac single phase system on Villupuram - Tiruchirappalli Section in Tiruchirappalli Division of Southern Railway.**

(No. E.320/X/RVNL/CRS.)

(Pro forma 10-01)

“PUBLIC NOTIFICATION”

No. SRO C-3/2015.

Notice is hereby given to all users of Railway lines and premises situated on the completed Section of the under-noted section of the Southern Railway that the 25000 Volt, 50 Hz, ac, single phase overhead traction wires will be energised on or after the date specified against the Section. On and from the same date the overhead traction line shall be treated as “LIVE” at all times and no unauthorised person shall approach or work in the proximity of the said overhead line.

Section	Date
Energisation of Overhead Equipment on the newly laid track, as part of doubling between Villupuram and Vridhachalam Town Stations, from OHE Mast No. 163/45A (km/ch:163/693.55) to OHE Mast No. 218/40 (km/ch : 218/978.85) at 25 kV, 50 Hz, ac single phase system on Villupuram - Tiruchirappalli Section in Tiruchirappalli Division of Southern Railway.	31-10-2014

Chennai-600 008,  
30th December 2014.

P. MANI,  
Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.

(No. E.320/X/RVNL/CRS.)

INTRODUCTION OF ac 25 kV TRACTION

(Pro forma 10-02)

“WARNING TO ROAD USERS”

No. SRO C-4/2015.

It is notified for information of the public that in connection with introduction of 25 kV ac electric traction on the newly laid track, as part of doubling between Villupuram and Vridhachalam Town Stations, from OHE Mast No. 163/45A (km/ch:163/693.55) to OHE Mast No. 218/40 (km/ch : 218/978.85) at 25 kV, 50 Hz, ac single phase System on Villupuram - Tiruchirappalli Section in Tiruchirappalli Division of Southern Railway, height gauges have been erected at all the level crossings with clear height of 4.67 m above road level with a view to prevent loads of excessive height from coming into contact or dangerous proximity to live traction wires.

Public are hereby notified to observe the height specified above for the purpose of loading vehicles and to see that the loads carried in road vehicles do not infringe the height gauges under any circumstances.

The dangers of a load of excessive height are as follows:

- i. Danger to the height gauge and consequent obstruction to the road as well as the Railway line.
- ii. Danger to the materials or equipment carried or for the vehicle itself.
- iii. Danger of fire and risk of life due to contact with or dangerous proximity to the conductors.

Chennai-600 008,  
30th December 2014.

P. MANI,  
Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.

**Energisation of Overhead Equipment on the newly laid 4th line between Tiruvallur and Tiruvalangadu Stations, from OHE Mast Location No. 41/35B (km/ch:41/902.50) to OHE Mast location No. 59/33A (km/ch : 59/938.33) at 25 kV, 50 Hz, ac single phase system on Chennai - Arakkonam Section in Chennai Division of Southern Railway.**

(No. E.320/X/RVNL/CRS.)

(Pro forma 10-01)

“PUBLIC NOTIFICATION”

No. SRO C-5/2015.

Notice is hereby given to all users of Railway lines and premises situated on the completed Section of the under-noted section of the Southern Railway that the 25000 Volt, 50 Hz, ac, single phase overhead traction wires will be energised on or after the date specified against the Section. On and from the same date the overhead traction line shall be treated as “LIVE” at all times and no unauthorised person shall approach or work in the proximity of the said overhead line.

<i>Section</i>	<i>Date</i>
Energisation of Overhead Equipment on the newly laid 4th line between Tiruvallur and Tiruvalangadu Stations, from OHE Mast location No. 41/35B (km/ch:41/902.50) to OHE Mast location No. 59/33A (km/ch : 59/938.33) at 25 kV, 50 Hz, ac single phase system on Chennai - Arakkonam Section in Chennai Division of Southern Railway.	31-1-2015

Chennai-600 008,  
30th December 2014.

P. MANI,  
*Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.*

(No. E.320/X/RVNL/CRS.)

INTRODUCTION OF ac 25 kV TRACTION

(Pro forma 10-02)

“WARNING TO ROAD USERS”

No. SRO C-6/2015.

It is notified for information of the public that in connection with introduction of 25 kV ac electric traction on the newly laid 4th line between Tiruvallur and Tiruvalangadu Stations, from OHE Mast location No. 41/35B (km/ch:41/902.50) to OHE Mast location No. 59/33A (km/ch : 59/938.33) at 25 kV, 50 Hz, ac single phase system on Chennai - Arakkonam Section in Chennai Division of Southern Railway, height gauges have been erected at all the level crossings with clear height of 4.67 m above road level with a view to prevent loads of excessive height from coming into contact or dangerous proximity to live traction wires.

Public are hereby notified to observe the height specified above for the purpose of loading vehicles and to see that the loads carried in road vehicles do not infringe the height gauges under any circumstances.

The dangers of a load of excessive height are as follows:

- i.* Danger to the height gauge and consequent obstruction to the road as well as the Railway line.
- ii.* Danger to the Materials or equipment carried or for the vehicle itself.
- iii.* Danger of fire and risk of life due to contact with or dangerous proximity to the conductors.

Chennai-600 008,  
30th December 2014.

P. MANI,  
*Deputy Chief Electrical Engineer/OHE  
for Chief Electrical Engineer,  
Southern Railway/Construction,  
Chennai, Egmore.*